

Especificaciones de Equipos con Filtros CELDEK o FRIOCEL 45/65 6" de Espesor 85/420 12" de Espesor

Modelo		PCM STD	Características Eléctricas			R. P. H.	C a í d a d e P r e s i ó n								Tamaño Ø Turbina
MCH	MCD		HP	VOLTS	AMP	TURBINA	0"	1/4"	1/2"	3/4"	1"	1 - 1/4"	1 - 1/2"		
4500	4500	4500	1/2	127	8.7	400	4104	3694		2992	2693	2423	2181	16" Ø	
6500	6500	6500	3/4		9.5	470	5200	4680	4212	3791	3412	3071	2763	19" Ø	
85	8500	8500	1	220	3.5	300	8480	7632	6869	6182	5564	5007	4507	24" Ø	
110	11000	11000	1		3.5	315	9328	8395	7556	6800	6120	5508	4957	24" Ø	
130	13000	13000	1 1/2	3 F	4.9	350	10505	3324	8509	7658	6892	6203	5583	24" Ø	
160	16000	16000	2		6.0	400	12760	11484	10336	9302	8372	7535	6781	24" Ø	
180	18000	18000	3	60c	8.7	453	14400	12960	11664	10498	9448	8503	7653	24" Ø	
210	21000	21000	5		13.5	500	17220	15498	13948	12553	11298	10168	9151	24" Ø	
250	25000	25000	5	(440)	13.5	400	23940	21546	19391	17452	15707	14136	12723	28" Ø	
320	32000	32000	7 1/2		20.0	450	25080	22572	20315	18283	16455	14809	13329	28" Ø	
360	36000	36000	10		27.0	489	28044	25240	22716	20444	18400	16560	14904	28" Ø	
420	42000	42000	15		39.0	543	34200	30780	27702	24932	22439	20195	18175	28" Ø	